



AG-319A High Clay DG 2 Mil

AG Organics AG-319A is our 2 Mil High Clay DG. Derived from crushing and screening naturally granite located in the Southern California area. Our High Clay DG provides a natural bonded surface due the higher clay content for pedestrian pathways and driveways while giving a superb natural landscape setting. This material will have a slight reddish / Gold color.

Gold with a slight Reddish tint in color.

AG-319B 2 Mil DG is also available with added stabilizer to help increase bonding partials together for less erosion in high traffic areas

RATES OF APPLICATION:

General preparation: For pathways, Stabilized decomposed granite shall be placed to a minimum depth of 3" compacted. For driveways or vehicular roadways Stabilized decomposed granite shall be placed to a minimum depth of 4" compacted over a DOT approved base.

For each 2" lift evenly spread the material over area of concern. Grade and smooth as desired. Thoroughly water entire area so that the entire depth of the material is moist. After a period of +/- 6 hours compact the finale lift with a 1000-3000lb drum roller. Allow for a sufficient curing period of +/- 4 days prior to use.

INGREDIENTS:

Crushing and screening natural granite and Clay.

GRADATION:

100% - 2 MM



AG ORGANICS, INC. P.O. BOX 20288 • RIVERSIDE, CA. 92516
Ph. 866-721-SOIL (7645) - Fax 951-780-2287
productspecs@agsoil.com